

7 USER MANUAL FOR DP C181.CAN



CONTENT

7.1 Important Notice.....	2	7.6.3 Selection Mode.....	5
7.2 Introduction of Display	2	7.6.4 Headlights / backlighting.....	6
7.3 Product Description.....	3	7.6.5 Walk Assistance.....	7
7.3.1 Specifications.....	3	7.6.6 SERVICE.....	7
7.3.2 Functions Overview.....	3	7.7 Settings.....	8
7.4 Display Information.....	4	7.7.1 "Display setting".....	8
7.5 Key Definition.....	4	7.7.2 "Information".....	10
7.6 Normal Operation.....	5	7.8 Error Code Definition.....	12
7.6.1 Switching the System ON/OFF.....	5		
7.6.2 Selection of Support Levels.....	5		

7.1 IMPORTANT NOTICE

- If the error information from the display cannot be corrected according to the instructions, please contact your retailer.
- The product is designed to be waterproof. It is highly recommended to avoid submerging the display under water.
- Do not clean the display with a steam jet, high-pressure cleaner or water hose.
- Please use this product with care.
- Do not use thinners or other solvents to clean the display. Such substances can damage the surfaces.
- Warranty is not included due to wear and normal use and aging.

7.2 INTRODUCTION OF DISPLAY

- Model: DP C181.CAN BUS
- The housing material is PC; the Display Glass is made of high-currentem material:



- The label marking is as follows:



- i** **Note:** Please keep the QR code label attached to the display cable. The information from the Label is used for a later possible software update.

7.3 PRODUCT DESCRIPTION


7.3.1 Specifications




- Operating temperature: -20 °C~45 °C
- Storage temperature: -20 °C~50 °C
- Waterproof: IP65
- Bearing humidity: 30%-70% RH

7.3.2 Functional Overview

- Speed display (including top speed and average speed, switching between km and miles).
- Battery capacity indicator.
- Automatic sensors explanation of the lighting system.
- Brightness setting for backlight.
- Indication of performance support.
- Motor output power and output current indicator.
- Kilometer stand (including single-trip distance, total distance and remaining distance).
- Walk assistance.
- Setting the support levels.
- Energy consumption indicator CALORIES (Note: If the display has this function).
- Display for the remaining distance. (Depends on your riding style)
- Key card function.
- Bluetooth function. (the display can connect to the mobile through Bafang Go APP)

7.4 DISPLAY INFORMATION




- 1 Time
- 2 USB charging indicator displays the icon , if an external USB device is connected to the display.
- 3 The display shows  this symbol, if the light is on.
- 4 Speed Graphics
- 5 Trip: Daily kilometers (TRIP) - Total kilometers (ODO) - Top speed (MAX) - Average speed (AVG) - Range (RANGE) - Energy Consumption (CALORIES(only with torque sensor fitted)) - Travel time (TIME).
- 6 Display of battery capacity in real time.
- 7 Maintenance indicator.
- 8 Bluetooth indicator.
- 9 Power indicator in watts / amperes.
- 10 Support level/ Walking assistance 
- 11 Data: Display data, which corresponds to the current mode.
- 12 Service: Please see the service section

7.5 KEY DEFINITION



7.6 NORMAL OPERATION



7.6.1 Switching the System ON/OFF


Press and hold  (>2S) on the display to turn on the system. Then place the key card close to the scanning area to unlock the system.

Press and hold  (>2S) again to turn off the system.

If the "automatic shutdown time" is set to 5 minutes (it can be set with the "Auto Off" function, See "**Auto Off**"), the display will automatically be turned off within the desired time when it is not in operation. If the password function is enabled, you must enter the correct password to use the system.

7.6.2 Selection of Support Levels

When the display is turned on, press the  or  (<0.5S) button to switch to the support level, the lowest level is 0, the highest level is 5. When the system is switched on, the support level starts in level 1. There is no support at level 0.



7.6.3 Selection Mode

Briefly press the  (0.5s) button to see the different trip modes.


Trip: daily kilometers (TRIP) - total kilometers (ODO) - Maximum speed (MAX) - Average speed (AVG) - Range (RANGE) - Energy consumption (CALORIES(only with torque sensor fitted)) - Travel time (TIME).



7.6.4 Headlights / backlighting







Hold the **+** (>2S) button to activate the headlight and taillights.


Hold the **+** (>2S) button again to turn off the headlight. The brightness of the backlight can be set in the display settings "**Brightness**". If the display /Pedelec is switched on in a dark environment, the display backlight/headlight will automatically be switched on. If the display backlight/headlight has been manually switched off, the automatic sensor function is deactivated. You can only turn on the light manually, after switching on the system again.



7.6.5 Walk Assistance


The Walk assistance can only be activated with a standing pedelec.

Activation: Press the  button until this symbol  appears. Next hold down the  button whilst the  symbol is displayed. Now the Walk assistance will activate. The symbol  will flashes and the pedelec moves approx. 6 km/h. After releasing the  button, the motor stops automatically and switches back to level 0.



7.6.6 SERVICE

The display shows "Service" as soon as a certain number of kilometers or battery charges has been reached. With a mileage of more than 5000 km (or 100 charge cycles), the "Service" function is displayed on the display. Every 5000 km the display "SERVICE" is displayed every time. This function can be set in the display settings.




7.7 SETTINGS

After the display is turned on, press and hold the **+** and **-** (>1S) button, to access the "SETTINGS" menu. By pressing the **+** or **-** (<0.5S) button, you can select: Display Settings, Information or EXIT. Then press the **⏻** (<0.5S) button to confirm your selected option.

Or select "EXIT" and press the **⏻** (<0.5S) button to return to the main menu, or select "BACK" and the **⏻** (<0.5S) button to return to the Settings interface.

If no button is pressed within 20 seconds, the display will automatically return to the main screen and no data will be saved.



You can press and hold the **+** and **-** (>1S) button at any time, to return to the main screen.


7.7.1 "Display setting"

Press the **+** or **-** (<0.5S) button to select Display Settings, and then briefly press the **⏻** (<0.5S) button to access the following selections.

Display Setting	
Unit	Metric
Service Tip	OFF
Brightness	100%
Auto Off	5Min
MAX PAS	5
Power View	Power
SOC View	Percent
TRIP Reset	NO
AI Sensitivity	3
Set Clock	>
BACK	

7.7.1.1 "Unit" Selections in km/Miles

Press the **+** or **-** (<0.5S) button to highlight "Unit" in the Display settings menu, and then press the **⏻** (<0.5S) button to select. Then with the **+** or **-** button choose between "Metric" (kilometer) or "Imperial" (Miles). Once you have chosen your desired selection, press the **⏻** (<0.5S) button to save and exit to the "Display setting" interface.



7.7.1.2 "Service" Switching the notification on and off

Press the **+** or **-** (<0.5S) button to highlight "Service" in the Display settings menu, and then press **⏻** (<0.5S) to select. Then with the **+** or **-** button choose between "ON" or "OFF". Once you have chosen your desired selection, press the **⏻** (<0.5S) button to save and exit to the "Display setting" interface.

7.7.1.3 "Brightness" Display brightness

Press the **+** or **-** (<0.5S) button to highlight "Brightness" in the Display settings menu. Then press **⏻** (<0.5S) to select. Then with the **+** or **-** button choose between "100%" / "75%" / "50%" / "30%" / "10%". Once you have chosen your desired selection, press the **⏻** (<0.5S) button to save and exit to the "Display setting" interface.

7.7.1.4 "Auto Off" Set Automatic system switch off time


Press the **+** or **-** (<0.5S) button to highlight "Auto Off" in the Display settings menu, and then press **⏻** (<0.5S) to select. Then with the **+** or **-** button choose between "OFF", "9"/"8"/"7"/"6"/"5"/"4"/"3"/"2"/"1", (The numbers are measured in minutes). Once you have chosen your desired selection, press the **⏻** (<0.5S) button to save and exit to the "Display setting" interface.

7.7.1.5 "MAX PAS" Support level

Press the **+** or **-** (<0.5S) button to highlight "Max Pass" in the Display settings menu, and then press **⏻** (<0.5S) to select. Then with the **+** or **-** button choose between "3/5/9" (the amount of support levels). Once you have chosen your desired selection, press the **⏻** (<0.5S) button to save and exit to the "Display setting"


7.7.1.6 "Power View" Setting the power indicator

Press the **+** or **-** (<0.5S) button to highlight "Power View" in the Display settings menu, and then press **⏻** (<0.5S) to select. Then with the **+** or **-** button choose between "Power" or "Current". Once you have chosen your desired selection, press the **⏻** (<0.5S) button to save and exit to the "Display setting" interface.



7.7.1.7 "SOC View" Battery view in volt percent

Press the **+** or **-** (<0.5S) button to highlight "SOC View" in the Display settings menu, and then press **⏻** (<0.5S) to select. Then with the **+** or **-** button choose between "percent" or "voltage". Once you have chosen your desired selection, press the **⏻** (<0.5S) button to save and exit to the "Display setting"



7.7.1.8 "TRIP Reset" Reset mileage

Press the **+** or **-** (<0.5S) button to highlight "TRIP Reset" in the Display settings menu, and then press **⏻** (<0.5S) to select. Then with the **+** or **-** button choose between "YES" or "NO". Once you have chosen your desired selection, press the **⏻** (<0.5S) button to save and exit to the "Display setting"

7.7.1.9 "AL Sensitivity" Automatic headlight sensitivity

Press the **+** or **-** (<0.5S) button to highlight "AL-Sensitivity" in the Display settings menu, and then press **⏻** (<0.5S) to select. Then with the **+** or **-** button choose between "0" / "1" / "2" / "3" / "4" / "5" / "OFF". Once you have chosen your desired selection, press the **⏻** (<0.5S) button to save and exit to the "Display setting"

7.7.1.10 "Set Clock"

Press the **+** or **-** (<0.5S) Button to highlight "Set Clock" in the Display settings menu. Then briefly press the **⏻** (<0.5S) button to confirm selection. Now press the **+** or **-** (<0.5S) button and input the correct number (time) and press the **⏻** (<0.5S) button to move to the next number. After entering the correct time, press the **⏻** (<0.5S) button to confirm and save.

7.7.1.11 "Vibration"

Press the **+** or **-** (<0.5S) Button to highlight "Vibration" in the Display settings menu. Then briefly press the **⏻** (<0.5S) button to confirm selection. Then press the **+** or **-** (<0.5S) button to choose between "ON" or "OFF". After entering the correct time, press the **⏻** (<0.5S) button to confirm and save.

7.7.2 "Information"

Once the system is turned on, press and hold the **+** and **-** (>1S) button to access the "SETTINGS" menu. Now by pressing the **+** or **-** (<0.5S) button, Highlight the "information" in the display Settings, and press the **⏻** (<0.5S) button confirm your selection.

Or select the point "Back" by confirming with the **⏻** (<0.5S) button to return to the main menu.

Information	
Wheel Size	27"
Speed Limit	25km/h
Battery Info	>
Ctrl Info	>
Display Info	>
Torque Info	>
Back	

7.7.2.1 Wheel Size and Speed Limit

The "Wheel Size" and "Speed Limit" cannot be changed, this information is here to be viewed only.

7.7.2.2 Battery Information

Press the **+** or **-** (<0.5S) button to access the "Battery Info" menu, and then press the **⏻** (<0.5S) button to select confirm. Now press the **+** or **-** (<0.5S) button and select "Back" or "Next Page". Then press the **⏻** (<0.5S) button to confirm, now you can read the battery information.

Content	Explanation
TEMP	Current temperature in degrees (°C)
TotalVolt	Voltage (V)
Current	Discharge (A)
Res Cap	Remaining Capacity (A/h)
Full Cap	Total Capacity (A/h)
RelChargeState	Default Loader Status (%)
AbsChargeState	Instant charge (%)

Content	Explanation
Cycle Times	Charging cycles (number)
Max Uncharge Time	Maximum time in which no charge was made (Hr)
Last Uncharge Time	
Total Cell	Number (individual)
Cell Voltage 1	Cell Voltage 1 (mV)
Cell Voltage 2	Cell Voltage 2 (mV)
Cell Voltage n	Cell Voltage n (mV)
HW	Hardware Version
SW	Software Version

NOTE: If no data is detected, "--" is displayed.

7.7.2.3 Controller Information

Press the **+** or **-** (<0.5S) button and select "CTRL Info", and then press the **⏻** (<0.5S) button to confirm. Now you can read the controller information. To Exit press the **⏻** (<0.5S) button, or select "Back" to return to the information interface.

Ctrl Info	
HW	*****
SW	*****
Back	

7.7.2.4 Display Information

Press the **+** or **-** (<0.5S) button and select "Display Info", then press the **⏻** (<0.5S)

button to read the software and hardware data in the display. To Exit press the **⏻** (<0.5S) button, or select "Back" to return to the information interface.

Display Info	
HW	*****
SW	*****
Back	

7.7.2.5 Torque Information

Press the **+** or **-** (<0.5S) button and select "Torque info", then press the **⏻** (<0.5S) button to read the software and hardware data in the display. To Exit press the **⏻** (<0.5S) button, or select "Back" to return to the information interface.


Torque Info	
HW	*****
SW	*****
Back	

7.7.2.6 Error Code

Press the **+** or **-** (<0.5S) button and select "Error Code", and then press the **⏻** (<0.5S) button to confirm. It shows error information for the last ten errors of the pedelec. Error code "00" means that there is no error. To Exit press the **⏻** (<0.5S) button, or select "Back" to return to the information interface.

7.8 ERROR CODE DEFINITION



The display can show the errors of a pedelec. If an error is detected, the wrench icon  appears on the display and one of the following error codes will be displayed.

Note: Please read the description of the error code carefully. If you see the error code, restart the system first. If the problem is not resolved, please contact your dealer.

Error	Declaration	Troubleshooting
04	The throttle is not back in its correct position.	Check the throttle can adjust back into its correct position, if the situation does not improve, please change to a new throttle.(only with this function)
05	The throttle has fault.	1. Check the connector of throttle whether they are correctly connected. 2. Disconnect the throttle, If the problem still occurs, please contact your retailer. (only with this function)
07	Overvoltage protection	1. Remove the battery. 2. Re-Insert the battery. 3. If the problem persists, please contact your retailer.
08	Error with the hall sensor signal inside the motor	Please contact your retailer.
09	Error with the Engine phase's	Please contact your retailer.
10	The temperature inside the engine has reached its maximum protection value	1. Turn off the system and allow the Pedelec to cool down. 2. If the problem persists, please contact your retailer.
11	The temperature sensor inside the motor has an error	Please contact your retailer.
12	Error with the current sensor in the controller	Please contact your retailer.
13	Error with the temperature sensor inside of the battery	Please contact your retailer.

Error	Declaration	Troubleshooting
14	The protection temperature inside the controller has reached its maximum protection value	<ol style="list-style-type: none"> 1. Turn off the system and let the pedelec cool down. 2. If the problem persists, please contact your retailer.
15	Error with the temperature sensor inside the controller	Please contact your retailer.
21	Speed sensor Error	<ol style="list-style-type: none"> 1. Restart the system 2. Check that the magnet attached to the spoke is aligned with the speed sensor and that the distance is between 10 mm and 20 mm. 3. Check that the speed sensor connector is connected correctly. 4. If the error persists, please contact your retailer.
25	Torque signal Error	<ol style="list-style-type: none"> 1. Check that all connections are connected correctly. 2. If the error persists, please contact your retailer.
26	Speed signal of the torque sensor has an error	<ol style="list-style-type: none"> 1. Check the connector from the speed sensor to make sure it is connected correctly. 2. Check the speed sensor for signs of damage. 3. If the problem persists, please contact your retailer.
27	Overcurrent from controller	Please contact your retailer.
30	Communication problem	<ol style="list-style-type: none"> 1. Check all connections are correctly connected. 2. If the error persists, please contact your retailer.
33	Brake signal has an error (If brake sensors are fitted)	<ol style="list-style-type: none"> 1. Check all connectors. 2. If the error continues to occur, please contact your retailer.

Error	Declaration	Troubleshooting
35	Detection circuit for 15V has an error	Please contact your retailer.
36	Detection circuit on the keypad has an error	Please contact your retailer.
37	WDT circuit is faulty	Please contact your retailer.
41	Total voltage from the battery is too high	Please contact your retailer.
42	Total voltage from the battery is too low	Please contact your retailer.
43	Total power from the battery cells is too high	Please contact your retailer.
44	Voltage of the single cell is too high	Please contact your retailer.
45	Temperature from the battery is too high	Please contact your retailer.
46	The temperature of the battery is too low	Please contact your retailer.
47	SOC of the battery is too high	Please contact your retailer.
48	SOC of the battery is too low	Please contact your retailer.
61	Switching detection defect	Please contact your retailer. (only with this function)
62	Electronic derailleur cannot release.	Please contact your retailer. (only with this function)
71	Electronic lock is jammed	Please contact your retailer. (only with this function)
81	Bluetooth module has an error	Please contact your retailer. (only with this function)