# 6 USER MANUAL FOR M410 (MM G333.250.C)



## **CONTENT**

6.1 Introduction	.2
6.2 Specifications.	.3
6.2.2 Surface	.3
6.2.3 Storage Information	3
6.3 Maintenance	1

## **6.1 INTRODUCTION**



Product Model
MM G333.250.C


#### · Scope of Application



Only apply to electric powered bicycles, and specifically designed or licensed for pedelec. It is suitable for mountain bikes. It should not be used for competition or other commercial purposes.

#### Identification

There are the unique identification of the product on the housing, as shown in figure:



Note: Contents in Label part are important information of this product. Please keep them properly for updating of software or providing after-sales service.

## **6.2 SPECIFICATIONS**

#### ① Motor model: MM G333.250.C

Rated power (W)	250
Rated voltage (V)	36 / 43 / 48
Waterproof	IP65
Certification	CE / ROHS / EN14766
Operating temperature	-20 °C~45 °C

#### 6.2.1 Surface

Shockproof black coating

### **6.2.2 Storage Information**

The pedelec should be stored in a ventilated humid and dry room. Avoid storing the pedelec near strong magnetic objects.

## **6.3 MAINTENANCE**

- Maintenance must be carried out by authorized personnel with the correct equipment.
- Do not disassemble the motor.
- Do not use thinners or other solvents to clean the components. Such substances can damage the surfaces.
- Avoid water submerging, to keep the components protected.
- · Avoid using high-pressure cleaning jets.
- For prolonged storage, turn off the battery and avoid storing near heat sources.